



Clinching Nut



D = Head Diameter
T = Head Thickness
P = Ring Diameter

*Dimensions in millimeters

Thread Size	P max.	Hole Size (+0.08)	K max.	Material Thickness min.	D app.	T	Dist. C/L hole edge min.
M2	4.22	4.25	0.75	0.8~1.0	6.30	1.50	4.8
M2			1.05	1.1~1.4			
M2			1.45	1.5~2.3			
M2			2.30	>2.4			
M2.5	4.22	4.25	0.75	0.8~1.0	6.30	1.50	4.8
M2.5			1.05	1.1~1.4			
M2.5			1.45	1.5~2.3			
M2.5			2.30	>2.4			
M3	4.22	4.25	0.75	0.8~1.0	6.30	1.50	4.8
M3			1.05	1.1~1.4			
M3			1.45	1.5~2.3			
M3			2.30	>2.4			
M3.5	4.73	4.75	0.75	0.8~1.0	7.10	1.50	5.6
M3.5			1.05	1.1~1.4			
M3.5			1.45	1.5~2.3			
M3.5			2.30	>2.4			
M4	5.38	5.40	0.75	0.8~1.0	7.90	2.00	6.7
M4			1.05	1.1~1.4			
M4			1.45	1.5~2.3			
M4			2.30	>2.4			
M5	6.35	6.40	0.75	0.8~1.0	8.70	2.00	7.0
M5			1.05	1.1~1.4			
M5			1.45	1.5~2.3			
M5			2.30	>2.4			
M6	8.72	8.75	1.35	1.4~2.3	11.05	4.08	8.7
M6			2.30	2.4~3.2			
M6			3.20	>3.3			
M8	10.44	10.50	1.35	1.4~2.3	12.65	5.47	9.5
M8			2.30	2.4~3.2			
M8			3.20	>3.3			
M10	13.90	14.00	2.20	2.3~3.2	17.35	7.50	11.0
M10			3.10	3.3~6.3			
M10			6.00	>6.3			
M12	16.90	17.00	3.10	3.3~6.3	20.55	8.50	16.0
M12			6.00	>6.3			